

<b>SPECIFICATIONS</b>	<b>Panther</b>	<b>SSX</b>	<b>Predator</b>
<b>ENGINE</b>	CUMMINS DIESEL L9 OR X12	CUMMINS L9, X12 OR X15	CUMMINS DIESEL L9 OR X12
<b>ENGINE HORSEPOWER</b>	380-525 HP	330-600 HP	400-600 HP
<b>TRANSMISSION</b>	ALLISON 3000 EVS OR 4000 EVS (Retarder Available)	ALLISON 3000 EVS, 4000 EVS, 4500 EVS*	ALLISON GEN V3000 EVS OR 4000 EVS (Retarder Available)
<b>FRONT GAWR (MAXIMUM)</b>	24,000 LBS.	24,000 LBS.	24,000 LBS.
<b>REAR GAWR (MAXIMUM)</b>	58,000 LBS.	33,500 LBS. SINGLE/60,000 LBS. TANDEM	63,000
<b>AXLE CONFIGURATIONS</b>	4X2, 6X4	4X2, 4X4, 6X4, 6X6	4X2, 6X4
<b>FRONT AXLE</b>	I BEAM, FABRICATED BEAM OR IFS	PARABOLIC OR MULTI-LEAF, STEERTEK NXT OR IFS	I BEAM, STEERTEK, OR IFS
<b>FRONT SUSPENSION</b>	IFS OR LEAF SPRING	IFS OR LEAF SPRING	IFS OR LEAF SPRING
<b>STEERING COLUMN/WHEEL</b>	18" TILT / TELESCOPIC (2- or 4-Spoke, SMARTwheel Visibility Available)	18" TILT / TELESCOPIC (2- or 4-Spoke, SMARTwheel Visibility Available)	18" TILT / TELESCOPIC (2- or 4-Spoke, SMARTwheel Visibility Available)
<b>FRONT AXLE TURNING RANGE</b>	35°, 42°, 43°, 44°L / 42°R, 48°, 48°L / 44°R, 50°, 53° OR 53°L / 50°R	35°, 42°, 43°, 44°L / 42°R, 48°, 48°L / 44°R, 50°, 53° OR 53°L / 50°R	35°, 42°, 43°, 44°L / 42°R, 48°, 48°L / 44°R, 50°, 53° OR 53°L / 50°R
<b>REAR AXLE</b>	SINGLE OR TANDEM	SINGLE OR TANDEM	SINGLE OR TANDEM
<b>REAR SUSPENSION</b>	AIR, RUBBER OR SPRING	MULTI-LEAF SINGLE, RUBBER, AIR, TANDEM	AIR, RUBBER OR SPRING
<b>BRAKES</b>	DISC OR DRUM	DISC OR "S" CAM BRAKES	DISC OR DRUM
<b>BRAKE SYSTEMS</b>	ABS / ATC / RSC / ESC	ABS / ATC / RSC / ESC	ABS / ATC / RSC / ESC
<b>WHEELBASE</b>	136" – 303.5" (1/2" increments)	136" – 303.5" (1/2" increments)	136" – 303.5" (1/2" increments)
<b>BUMPER EXTENSIONS</b>	6" / 8" / 12.5" / 14" / 16" / 18" / 21" / 24" / 28" / 31"	6" / 8" / 12.5" / 14" / 16" / 18" / 21" / 24" / 28" / 31"	6" / 8" / 12.5" / 14" / 16" / 18" / 21" / 24" / 28" / 31"
<b>BATTERIES</b>	3 BCI OR 6 BCI GROUP 31	3 BCI OR 6 BCI GROUP 31	3 BCI OR 6 BCI GROUP 31
<b>ALTERNATOR</b>	270, 300, 320, 325, 360 OR 420 AMP	270, 300, 320, 325, 360 OR 420 AMP	270, 300, 320, 325, 360 OR 420 AMP
<b>KEYLESS</b>	START, ENTRY* (touch pad) AND ANTI THEFT*	START, ENTRY* (touch pad) AND ANTI THEFT*	START, ENTRY* (touch pad) AND ANTI THEFT*
<b>SEATING CAPACITY</b>		UP TO 8	
<b>DOOR STYLE</b>		BARRIER OR FULL HEIGHT	
<b>CAB ROOF STYLE</b>		FLAT, RAISED 10", 16", 22"	
<b>ELECTRICAL SYSTEM</b>		HARD-WIRED OR MULTI-PLEX (CLASS ONE, WELDON)	
<b>4X4 SYSTEM</b>		MERITOR T-CASE, DANA POWER DIVIDER, EX-TRAC HYDRAULIC AWD	