

SPECIFICATIONS	102' Rear Mount Platform	84' Mid Mount Platform	102' Mid Mount Platform	
Chassis Type	PREDATOR, SSX	PREDATOR, SSX	PREDATOR, SSX	
Vertical Reach	102'	84'	102'	
Horizontal Reach	92'	77'	94'	
Operating Range	-12° TO 80°	-12° TO 80°	-12° TO 80°	
Tip Load with Water	500 LBS	500 LBS	500 LBS	
Tip Load without Water	1000 LBS	1000 LBS	1000 LBS	
Wind and Ice Rating	50 MPH AND 1/4" ICE ON ENTIRE STRUCTURE	50 MPH AND 1/4" ICE ON ENTIRE STRUCTURE	50 MPH AND 1/4" ICE ON ENTIRE STRUCTURE	
Water Flow	3000 GPM	3000 GPM	2000 GPM	
Stabilizer Style	H-STYLE	H-STYLE	H-STYLE	
Stabilizer Stance	18'	18'	18'	
REAR AXLE	TANDEM	TANDEM	TANDEM	
Tank Capacities	UP TO 300 GALLONS	UP TO 300 GALLONS	UP TO 300 GALLONS	
Pump Range				
Hosebed Capacity				
Ladder Compliment	NFPA OR ISO COMPLIMENTS	NFPA OR ISO COMPLIMENTS	NFPA OR ISO COMPLIMENTS	
Ladder Warranty	20-YEAR STRUCTURAL	20-YEAR STRUCTURAL	20-YEAR STRUCTURAL	