



TRACTOR-DRAWN AERIAL ✓

SUPERIOR PERFORMANCE. MAXIMUM MANEUVERABILITY. ✓

KME Tractor-Drawn Aerials with Steel-Safe™ Technology are known for their maneuverability with the shortest wheelbase and overall length available in the industry. The addition of Steertek™ NXT on the tractor steer axle provides a 45-degree cramp angle and a 28-degree cramp angle when added to the trailer steering axle for even more maneuverability.

Choose from two models, a 100-foot ladder with no waterway or a 101-foot ladder with a pre-piped waterway. Transform your TDA into an NFPA 1901 compliant quint with the addition of a pump and tank that gives you the flexibility your department needs.



NO-POST VISION KEEPS MAXIMUM MANEUVERABILITY AND SAFETY IN MIND.

TRACTOR-DRAWN AERIAL ↙



EXTREME DUTY. HIGH PERFORMANCE.



ELEVATING PERFORMANCE

Maximum maneuverability is the name of the game with our tractor-drawn aerials, featuring the shortest wheelbase and overall length in the industry with over 500 cubic feet of storage space.



SPECIFICATIONS

	100' TDA LADDER	101' TDA LADDER (WATERWAY)
CHASSIS TYPE	PANTHER, PREDATOR™, SSX™	PANTHER, PREDATOR™, SSX™
VERTICAL REACH	100'	101'
HORIZONTAL REACH	94'	94'
OPERATING RANGE	7° TO 80°	7° TO 80°
LADDER CAPACITY WITH WATER	500 LBS.	500 LBS.
LADDER CAPACITY W/OUT WATER	N/A	500 LBS.
WIND AND ICE RATING	50 MPH AND ¼" ICE ON ENTIRE STRUCTURE	50 MPH AND ¼" ICE ON ENTIRE STRUCTURE
WATER FLOW	N/A	1,500 GPM
STABILIZER STYLE	H-STYLE	H-STYLE
STABILIZER STANCE	14' FRONT	14' FRONT
TANK CAPACITIES	UP TO 350 GALLONS	UP TO 350 GALLONS
PUMP RANGE	250-2,500 GPM	250-2,500 GPM
HOSE BED CAPACITY	UP TO 800'	UP TO 800'
LADDER COMPLEMENT	NFPA OR ISO COMPLEMENTS	NFPA OR ISO COMPLEMENTS
LADDER WARRANTY	20-YEAR STRUCTURAL	20-YEAR STRUCTURAL

Technical specifications and descriptions are subject to change without notice. Content is limited and does not cover all available features. For additional information, please contact a KME Regional Sales Manager.



800-235-3928 | KMEFIRE.COM |

© 2023 REV Group, Inc. All Rights Reserved.