



----- CHASSIS -----

CHASSIS: 100"W SEVERE SERVICE 4X2  
 CAB: XLFD WITH 10" RAISED ROOF  
 ENGINE: CUMMINS ISX 15 600 HP  
 TRANSMISSION: ALLISON 4000EVS  
 FRONT AXLE: 23,000 LB  
 REAR AXLE: 31,000 LB

----- PUMP -----

PUMP: WATEROUS CMU-C20; 2,000 GPM TWO STAGE  
 INTAKES  
 DRIVER SIDE: 6" & 3"  
 OFFICER SIDE: 6" & 3"  
 FRONT: N/A  
 REAR: N/A  
 DISCHARGES  
 DRIVER SIDE: (2) 2-1/2"  
 OFFICER SIDE: (1) 4" & (1) 3"  
 FRONT: N/A  
 REAR: (2) 2 1/2" DS & (1) 3" OS  
 DECK GUN: (1) 3" CENTER OF DUNNAGE  
 OTHER: (1) 2 1/2" & (1) 1 3/4" SPEEDLAYS  
 (1) BOOSTER REEL

----- TANK -----

TANK: POLY  
 WATER: 500 GALLONS  
 FOAM: N/A  
 EXTRA FILLS: N/A  
 DUMPS: N/A

----- BODY -----

BODY TYPE: 172" FLEX LONG  
 MATERIAL: 3/16" ALUM  
 COMPARTMENTATION  
 DRIVER SIDE: FULL HEIGHT/FULL DEPTH  
 OFFICER SIDE: FULL HEIGHT/FULL DEPTH  
 HOSEBED  
 DIVIDERS: FOUR (4)  
 HOSE LOAD: 200' OF 1-3/4" - DS OUTER  
 200' OF 1-3/4" - DS INNER  
 1,000' OF 5" - DS CENTER  
 900' OF 3" - OS CENTER  
 200' OF 2-1/2" - OS OUTER

----- MISC. -----

GENERATOR: HARRISON MPC 20KW  
 FOAM SYSTEM: N/A

CUSTOMER APPROVAL:

NAME: \_\_\_\_\_  
 TITLE: \_\_\_\_\_  
 DATE: \_\_\_\_\_

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS. CONTRACT SPECIFICATIONS SHALL PREVAIL OVER DRAWING

E	DATE	REVISION DESCRIPTION	MPH
E	08-30-17	REVISED BODY	MPH
SYM	DATE	REVISION DESCRIPTION	APP'D

SALES ENGINEER : MARK P. HIGGINS



KOVATCH MOBILE EQUIPMENT  
 ONE INDUSTRIAL COMPLEX - NESQUEHONING, PA 18240  
 DIMENSIONS ARE APPROXIMATE & MAY VARY DUE TO BUILD ADJUSTMENTS  
 DATE: 3-8-16 SCALE: 1"=24" DWG SIZE: D DRAWN BY: Z.ZSCHUNKE  
 APPROVED BY: T.MAFF

KME CUSTOM PUMPER  
 GEORGE CLAY FIRE COMPANY, PA  
 GSO #10503