



**\*\* NOTE \*\***  
 OVERALL HEIGHT  
 12R TIRE = CURRENT  
 315 TIRE ADD 1 1/4"  
 425 TIRE ADD 2"

**----- CHASSIS -----**

CHASSIS: 100"W KME PREDATOR LFD  
 CAB: 4 DOOR WITH 10" RAISED ROOF  
 ENGINE: CUMMINS ISX15 500 HP  
 TRANSMISSION: ALLISON 4000EVS  
 FRONT AXLE: 22,500 LB MERITOR  
 REAR AXLE: 31,000 LB

**----- PUMP -----**

PUMP: WATEROUS CSU-C20- 1500 GPM SINGLE STAGE  
**INTAKES**  
 DRIVER SIDE: 6" & 2-1/2"  
 OFFICER SIDE: 6" & 2 1/2"  
 FRONT: 6"  
 REAR: N/A  
**DISCHARGES**  
 DRIVER SIDE: (2) 2-1/2"  
 OFFICER SIDE: (1) 4" & (1) 2-1/2"  
 FRONT: (1) 2 1/2"  
 REAR: (2) 2 1/2", 1 EACH SIDE  
 DECK GUN: (1) 3"  
 OTHER: (2) 1-3/4" & (1) 2 1/2" CROSSLAYS  
 (1) BOOSTER REEL

**----- TANK -----**

TANK: POLY  
 WATER: 1,000 GALLONS  
 FOAM: N/A  
 EXTRA FILLS: N/A  
 DUMPS: N/A

**----- BODY -----**

BODY TYPE: 147" FLAT BACK  
 MATERIAL: 12 GA 304L STAINLESS STEEL  
**COMPARTMENTATION**  
 DRIVER SIDE: FULL HEIGHT/SPLIT DEPTH  
 OFFICER SIDE: FULL HEIGHT/SPLIT DEPTH  
**HOSEBED**  
 DIVIDERS: THREE (3)  
 HOSE LOAD: 400' OF 1 3/4"  
 1,500' OF 5"  
 300' OF 3"  
 400' OF 1 3/4"

**----- MISC. -----**

GENERATOR: ONAN 10,000 WATT MOBILE PTO/HYD  
 FOAM SYSTEM: N/A

**CUSTOMER APPROVAL:**

NAME: \_\_\_\_\_  
 TITLE: \_\_\_\_\_  
 DATE: \_\_\_\_\_

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS. CONTRACT SPECIFICATIONS SHALL PREVAIL OVER DRAWING


A	06/17/16	BODY DESIGN	KS
SYM	DATE	REVISION DESCRIPTION	APP'D

SALES ENGINEER : KEVIN STEBER



KOVATCH MOBILE EQUIPMENT  
 ONE INDUSTRIAL COMPLEX - NESQUEHONING, PA 18240  
 DIMENSIONS ARE APPROXIMATE & MAY VARY DUE TO BUILD ADJUSTMENTS

DATE	SCALE	DWG SIZE	DRAWN BY
09/23/15	1"=24"	D	J.J.M
APPROVED BY		KS	

**KME CUSTOM PUMPER**

ORANGE LAKE, NY

GSO#10242 - 10243

